



600 Gallon Platform Series

850 McFarland Parkway - Alpharetta, GA 30004 www.usjetting.com / sales@usjetting.com 1-800-JETTING / 770-740-9917 / Fax: 770-740-0297

Central Control Panel Attached To Swivel Hose Reel; Optional Wireless Remote Control

325 Gallon Rotationally Moulded High Density Polyethylene (HDPE) Water Tank

Available Diesel Engines:

- Hatz Silent Pack Diesel
- Hatz Non-Silent Diesel
- Kubota TurboCharged Diesel

Hydraulic Powered, 7 Position Swivel Hose Reel With 500 Feet Of 1/2", 5/8" or 3/4" High Pressure Jetting Hose

Self-Contained Anti-Freeze System

Lockable Tool Boxes On Each Side

US Jetting Run-Dry Pump

Pressures Up To 5,000 PSI
Flows Of 14, 18, 25 or 40 GPM

2" x 4" Welded Steel Frame

Rust Free Powder Coated Aluminium Components

- Toolboxes
- Anti-Freeze Tank
- Diesel Fuel Tank
- Fenders
- Control Panel

Jump Jet Pulsation System

Tandem 6,000 Lb. Torque Flex Axle With 16" Tires & Chrome Wheels (Electric or Hydraulic Braking System)



Optional Single or Dual Power Pull-Out Hydraulic Hose Reels



Hose reels can be equipped with 1/2", 5/8" or 3/4" high pressure jetting hose to match any US Jetting PumpSet

Features

- Gen 4 Wireless Remote Control System (Optional)
- Single Hydraulic Power Pull-Out, 7-Position Hose Reel (Optional)
- Dual Hydraulic Power Pull-Out, 7-Position Hose Reels (Optional)
- Self-Contained Anti-Freeze System or Double
- Dual 325 Gallon Rotationally Molded HDPE Tanks
- Dual 375 Gallon Rotationally Molded HDPE Tanks (Opt.)
- 3 Rear, 1 Forward RPD Nozzle (Standard)
- 6 Rear RPD Nozzle (Standard)
- Powder Coat / Baked Finish
- Lockable Control Panel
- Jump Jet Pulsation System
- 2" x 4" Tubular Steel Frame Construction
- 16" Tires, with 8 Lug Chrome Wheels
- Analog & LED Pressure Gauges
- Electric or Hydraulic Brake Systems
- Tandem 6,000 Lb. TorqueFlex Axles
- Handheld Spotlight
- Dual Lockable Tool Boxes
- Traffic Safety Warning Light
- Tiger Tail Hose Protector
- Optional Custom Paint
- Drain Jet Extension
- Water Flow ByPass System

| US Jetting Pump Model | Engine (Diesel) | Horsepower | PSI | GPM | Hose Dia. | Hose Length (Std.) | Pump Cyls. | Jump Jet | Flow Bypass Valve |
|---------------------------------|---------------------------|------------|-------|-----|-----------|--------------------|------------|----------|-------------------|
| USJ 4018 Run-Dry Pump | Hatz 3-Cyl SilentPack | 49 | 4,000 | 18 | 1/2" | 500' | 3 | Std. | Std. |
| | Hatz 3-Cyl Non-Silent | 49 | 4,000 | 18 | 1/2" | 500' | 3 | Std. | Std. |
| | Kubota 4-Cyl Turbocharged | 49 | 4,000 | 18 | 1/2" | 500' | 3 | Std. | Std. |
| USJ 4025 Run-Dry Pump | Hatz 4-Cyl SilentPack | 66 | 4,000 | 25 | 5/8" | 500' | 3 | Std. | Std. |
| | Kubota 4-Cyl Turbocharged | 84 | 4,000 | 25 | 5/8" | 500' | 3 | Std. | Std. |
| USJ 5014 Run-Dry Pump | Hatz 3-Cyl SilentPack | 49 | 5,000 | 14 | 1/2" | 500' | 3 | Std. | Std. |
| USJ 5014 Run-Dry Pump | Hatz 3-Cyl Non-Silent | 49 | 5,000 | 14 | 1/2" | 500' | 3 | Std. | Std. |
| USJ 5018 Run-Dry Pump | Hatz 4-Cyl SilentPack | 66 | 5,000 | 18 | 1/2" | 500' | 3 | Std. | Std. |
| USJ 6018 Run Dry Pump | Kubota 4-Cyl Turbocharged | 84 | 6,000 | 18 | 1/2" | 500' | 3 | Std. | Std. |
| USJ 2036 | Hatz 3-Cyl SilentPack | 49 | 2,000 | 40 | 3/4" | 500' | 3 | Std. | Std. |
| | Hatz 3-Cyl Non-Silent | 49 | 2,000 | 40 | 3/4" | 500' | 3 | Std. | Std. |
| | Kubota 4-Cyl Turbocharged | 49 | 2,000 | 40 | 3/4" | 500' | 3 | Std. | Std. |
| USJ 2040 | Kubota 4-Cyl Turbocharged | 84 | 2,000 | 50 | 3/4" | 500' | 3 | Opt. | Std. |
| USJ 2040 | Hatz 4-Cyl Silent Pack | 55 | 2,000 | 50 | 3/4" | 500' | 3 | Opt. | Std. |
| USJ 3040 | Kubota 4-Cyl Turbocharged | 99 | 3,000 | 40 | 3/4" | 500' | 3 | Std. | Std. |



See More At
www.usjetting.com